

Bulker Unloading and Dual Feeding System



Bulker Unloading System

*Cement Feeding System
(Dual Feeding System)*



- Closed System
- Ensures contamination free transfer for material
- No Spillage or wastage involved
- Minimum Maintenance
- Speedy & User friendly designs

TECHNICAL SPECIFICATIONS

Bulker Unloading System

- Twin lobe blower- USHA/ KULKARNI MAKE Air volume—850 m³/h, pressure 0.7 kg/cm²(g)max., Motor 37.5 kw/4p. Accessories- Inlet filter cum silencer, pressure gauge, pressure switch, safety relief valve, V- belt and pulleys, belt guard.
- Motor Starter for 50 HP. (BBL)
- Motor 37.5 kw/4p (BBL)

Dual Feeding System

DESCRIPTION	SPECIFICATION
MODEL	PSP-II
OUTPUT CAPACITY*	20-25 TON/HR
FEED HOPPER CAPACITY	700 Kg
SCREW	TOUGHEND
SCREW MOTOR	22.5 kW / 30 HP (BBL)
TWIN LOBE AIR BLOWER	PI-22
BLOWER MOTOR	37.5 kW / 50 HP (BBL)
STRUTURE	ANTI VIBRATION PAD
POWER SUPPLY	440 V AC \pm 10%, 3 PHASE, 50 HZ \pm 5%
HOSE PIPE WITH ADEPTOR	114 MM ID – 5m; 101 MM ID – 7m
Accessories (Included):	
Suction Silencer	Driven Pulley
Discharge Silencer	Non Return Valve
Spring Loaded safety Valve	V-Belt Set
Pressure gauge	V- Belt Guard
Suction Filter	Drive Pulley

In accordance with its policy of constant product development, BHAI reserves the right to change the specifications without any prior notification. All dimensions and capacities quoted are nominal. Accessories shown are not a part of the supply.

MANUFACTURING UNIT:

BHAI PUMPCRETE (P) LTD.
VPO, BUDHEWAL,
CHANDIGARH ROAD,
LUDHIANA – 141 112



SALES & SERVICE:

BHAI PUMPCRETE (P) LTD.
B II/3, Mohan Cooperative Industrial Estate,
Badarpur, New Delhi - 110 044
Tel: +91-11-40505998
E-mail: sales@bhai.co.in